


PN10/16 B-type Flanged Y strainer



Specifications

Basic standard
<ul style="list-style-type: none"> Face to face: DIN3202-F1 Flange end: DIN2532/2533
Feature
<ul style="list-style-type: none"> Nominal Pressure (mpa): 1.6 Testing(water): 2.4mpa Suitable temperature: -10~200℃ Suitable medium: oil,gas,water


Main parts and materials

Part Name	Material
Body	GG25
Filter	SS304
Gasket	08+Graphite
Bonnet	GG25

Dimensions

DN	L	D	D1	D2	b-f	Z×Φd	L1	L2
50	230	Φ165	Φ125	Φ99	20-3	4×Φ19	102	140.5
65	290	Φ185	Φ145	Φ118	20-3	4×Φ19	112	161
80	310	Φ200	Φ160	Φ132	22-3	8×Φ19	138	184
100	350	Φ220	Φ180	Φ156	24-3	8×Φ19	165	222
125	400	Φ250	Φ210	Φ184	26-3	8×Φ19	191	257
150	480	Φ285	Φ240	Φ211	26-3	8×Φ23	214	290
200	600	Φ340	Φ295	Φ266	30-3	12×Φ23	275	363
250	730	Φ405	Φ355	Φ319	32-3	12×Φ28	330	434
300	850	Φ460	Φ410	Φ370	32-3	12×Φ28	387	542

PN10/16 Swing Check Valve



Specifications

Basic standard
<ul style="list-style-type: none"> Design and manufacture: BS EN 12334 Face to face: DIN3202-F6 Flange end: DIN2531/2532/2533
Feature
<ul style="list-style-type: none"> Nominal Pressure (mpa): 1.6 Shell test: 2.4mpa Seal test: 1.8mpa Suitable temperature: ≤200℃

Main parts and materials

Part Name	Material
Body	GG25
Seat	Brass/SS
Disc Seal Ring	Brass/SS
Disc	GG25
Bonnet	GG25

Dimensions

DN	L	D	D1	D2	b-f	Z×d	H
50	200	165	125	99	20-2	4×19	115
65	240	185	145	118	20-2	4×19	130
80	260	200	160	132	22-2	8×19	147
100	300	220	180	156	24-2	8×19	166
125	350	250	210	184	26-2	8×19	188
150	400	285	240	211	26-2	8×23	217
200	500	340	295	266	30-2	12×23	275