


20K Lift Check Valve

20SN
U.B.



E-E dimension : KITZ Std.
End threads : JIS B 0203

120°C Static water..... 2.8MPa
220°C Steam, air, gas, oil..... 2.5MPa
300°C Steam, air, gas, oil..... 2.3MPa
350°C Steam, air, gas, oil..... 2.0MPa

● Use for lubricating or hydraulic oil is acceptable.

Materials

Parts	JIS material
Body	FCD-5
Bonnet	SCS1
Disc	SCS13A + HF *
Bonnet ring	FCD-5
Gasket	Non-asbestos Sheet
Body seat ring	SCS13A + HF *


* Hard-faced with Co-Cr-W alloy

Dimensions

Size	mm						
	mm	15	20	25	32	40	50
	inch	1/2	3/4	1	1 1/4	1 1/2	2
L		78	91	105	122	135	160
H		56	60	68	80	85	99

20K Lift Check Valve

20SNB
U.B.
RF-flanged



F-F dimension : JIS B 2002 JV 4-4
End flanges : JIS B 2239 20K

120°C Static water..... 2.8MPa
220°C Steam, air, gas, oil..... 2.5MPa
300°C Steam, air, gas, oil..... 2.3MPa
350°C Steam, air, gas, oil..... 2.0MPa

● Use for lubricating or hydraulic oil is acceptable.

Materials

Parts	JIS material
Body	FCD-5
Bonnet	SCS1
Disc	SCS13A + HF *
Bonnet ring	FCD-5
Gasket	Non-asbestos Sheet
Body seat ring	SCS13A + HF *

* Hard-faced with Co-Cr-W alloy

Dimensions

Size	mm						
	mm	15	20	25	32	40	50
	inch	1/2	3/4	1	1 1/4	1 1/2	2
L		110	120	130	160	180	230
H		56	60	68	80	85	99

NOTE : For flange dimensions, refer to Page 40.