



Main parts and materials / Specification

Body, Bonnet	Grey iron
Buffer	NBR
Applicable Fluid	Water
Working Pressure	Less than 10kgf/cm ² (Max.1.0Mpa)
Applicable Temperature	Less than 60°C
Connection Method	10K FF Flange
Hydraulic Test	15kgf/cm ² (1.5Mpa)

Outline and connecting measurement

Size	40	50	65	80	100	125	150
D	140	155	175	185	210	250	280
b	20	20	21	21	22	22	23
H	180	185	199	211	230	246	255

*본 제품의 규격 및 사양은 성능 개선을 위해 예고없이 변경될 수 있습니다.



KOREA

Main parts and materials / Specification

Body	SPPS/STEEL PLATE
Trim	SWRH
Applicable Fluid	Water
Working Pressure	0.98MPa이하/1.96MPa이하
Applicable Temperature	Less than 60°C
Connection Method	10K, 20K Flange
Hydraulic Test	1.5MPa / 3.0Mpa

Outline and connecting measurement

Size	40	50	65	80	100	125	150	200
H	145	145	160	160	170	210	240	250
ΦD	140	155	175	185	210	250	280	330

*본 제품의 규격 및 사양은 성능 개선을 위해 예고없이 변경될 수 있습니다.



Main parts and materials / Specification

Body, Bonnet	Grey iron	
Trim	GC200/Rubber	
Rod pin	SCPH2	
Axle pin	STS 420J1-B	
Applicable Fluid	Water	
Working Pressure	10kgf/cm ² or less	
Applicable Temperature	80°C or less	
Connection Method	10K FF Flange	
Hydraulic Test	Body	15kgf/cm ² (1.5Mpa)
	Seat	11kgf/cm ² (1.1Mpa)

Outline and connecting measurement

Size	40	50	65	80	100	125	150	200	250
H	150	162	167	177	206	256	302	356	397
D	140	155	175	185	210	250	280	330	400

*본 제품의 규격 및 사양은 성능 개선을 위해 예고없이 변경될 수 있습니다.