



Teknik detaylar / Technical Specifications

- 1-Design as per DIN3356-1
- 2-End Flange DIN2533
- 3-Face to Face Dimension: DIN3202-F1
- 4-Test Standard:DIN3230



ÇAP SIZE	PN 16				
	L	D	D1	N-Ø	H
DN15	130	95	65	4*14	174
DN20	150	105	75	4*14	176
DN25	160	115	85	4*14	207
DN32	180	140	100	4*18	207
DN40	200	150	110	4*18	210
DN50	230	165	125	4*18	225
DN65	290	185	145	4*18	250
DN80	310	200	160	8*18	260
DN100	350	220	180	8*18	345
DN125	400	250	210	8*18	370
DN150	480	285	240	8*22	430
DN200	600	340	295	12*22	488
DN250	730	405	355	12*26	530
DN300	850	460	410	12*26	600

ÜRÜN AÇIKLAMASI / PRODUCT DESCRIPTION :

Metal körüklü glob vanalar;buhar,soğuk ve sıcak su,kızgın yağ v.s akış kontrolleri için kaliteli sızdırmazlığa sahip,bakım gerektirmeyen ürünlerdir.Metal körük sayesinde dış ortam ile akışkan arasında set oluşturarak sızıntıyı minimize ederler.Çevre dostudurlar. Açma-kapama kolaylığından ve volanın yerinde hareketi dolayısıyla yerden kazanç sağlarlar.Metal körük yüksek korozyona mukavemettir. Tesisat için ideal bir armatürdür.

Bellows seal globe valves have superior sealing capability and maintenance free operation for steam cold-hot water, hot oil etc. The bellows act as a barrier between external media and fluid, minimize leaks.Environmentally friendly. Since the stem does not raise during opening they can be operated in narrow places.The bellows are highly resistant to corrosion.An ideal armatüre for mains.

ÇALIŞMA ŞARTLARI / OPERATING CONDITIONS

MAX. TEST BASINÇI / MAX. TEST PRESSURE PMA (BAR)	24
MAX. SICAKLIK / MAX. TEMPERATURE TMA (°C)	350
MAX. ÇALIŞMA BASINCI / MAX. OPERATING PRESSURE PMO (BAR)	16

YEDEK PARÇALAR / SPARE PARTS

NO	AÇIKLAMA / DESCRIPTION	MALZEME / MATERIAL
1	GÖVDE / BODY	GS-C25+13Cr
2	DİSK / DISC	PASLANMAZ ÇELİK / SS304
3	PİM / PIN	PASLANMAZ ÇELİK / SS304
4	KÖRÜK / BELLOWS	PASLANMAZ ÇELİK / SS304
5	CONTA / GASKET	GRAFİT + PASLANMAZ ÇELİK / GRAPHITE+SS304
6	CİVATA / BOLT	B7
7	SOMUN / NUT	2H
8	KAPAK / COVER	ÇELİK DÖKÜM / GS-C25
9	SALMASTRA / PACKING	GRAFİT / GRAPHITE
10	SALMASTRA YUVASI / GLAND	13Cr
11	PİM / PIN	25
12	YATAKLAMA / BEARING	KARBON ÇELİK / CARBON STEEL
13	MİL / SHAFT	PASLANMAZ ÇELİK / SS304
14	MİL SOMUNU / SHAFT NUT	BAKIR ALAŞIM / CU ALLOY
15	VOLAN / HANDWHEEL	KARBON ÇELİK / CARBON STEEL
16	KİLİT SOMUNU / LOCK NUT	ALÜMİNYUM ALAŞIM / ALUMINUM ALLOY

BAĞLANTI ŞEKLİ / CONNECTION	FLANŞLI / FLANGED													
ÇAPLAR / SIZES	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	DN125	DN150	DN200	DN250	DN300
AĞIRLIKLAR / WEIGHTS (KGS)	4,5	5	5,8	7,5	10	12,5	18,5	23	38,5	53	81	144	230	450